

Flush-mounted two-button switch with illumination Pearl, 10A, 250V, WP-2P/S, white

ORNO

Marka: Orno | Symbol: OR-OE-7701/P/W | Ean: 5904988910823



PRODUCT DESCRIPTION

Modular series with a symmetrical frame plate system (for 1-, 2-, 3-, 4-, 5-modules) allowing the product to be mounted in both horizontal and vertical positions. The modern quick-connect mechanism (wires are connected by pushing them directly into the body) provides secure and safe wire installation and removal. The sockets are equipped with traditional screw connections. The internal design of the terminals guarantees secure connection of wires from 0.75 mm to 2.5 mm scheme and robust mounting plate grid and high-quality self-retracting elements enable stable and secure installation in the box. Special springing elements facilitate



fitting the frame into the body.

The two-button switch with illumination is adapted to flush mounting. Product is used to control lighting, for example, composed of chandeliers and traditional or modern LED bulbs. It allows you to switch lighting on and off, divided into two or more zones. In addition, this model is equipped with backlighting – so it will be perfect wherever the visibility of the button is important. It should be used indoors (IP20).

The product is available in two colors: white and black. Dimensions 81x81x41mm.

<u>에</u> ହ

€

TECHNICAL DATA

General information:

Wiring system:	Łącznik 2-biegunowy
Method of operation:	Przycisk wahadłowy
Assembly arrangement:	Element systemu modułowego do osprzętu elektroinstalacyjnego
Number of rockers:	2
Mounting method:	Montaż podtynkowy
Type of fastening:	Montaż pazurkowy /-śrubowy
Material:	Tworzywo sztuczne
Material quality:	Tworzywo termoplastyczne
Surface protection:	Malowanie
Surface finishing:	Błyszczący
Colour:	Biały
Label space/information surface:	Nie
Illumination:	Tak
Function lighting:	Orientacyjne
Suitable for degree of protection (IP):	IP20
Nominal voltage [V]:	250
Frequency [Hz]:	50
Rated current [A]:	10
Connection type:	Wtyk samozaciskowy



Device width [mm]:	81
Device height [mm]:	81
Device depth [mm]:	14
Built-in depth [mm]:	27
Min. depth of built-in installation box [mm]:	27









