

## Flush-mounted single socket 2P+E with charger USB A+C Pearl, 16A, 250V, PT-16P/USB, anthracite

**ORNO**

Marka: Orno | Symbol: OR-OE-7705/USBAC/A | Ean: 5904988915798



### PRODUCT DESCRIPTION

Modular series with a symmetrical frame plate system (for 1-, 2-, 3-, 4-, 5-modules) allowing the product to be mounted in both horizontal and vertical positions. The modern quick-connect mechanism (wires are connected by pushing them directly into the body) provides secure and safe wire installation and removal. The sockets are equipped with traditional screw connections. The internal design of the terminals guarantees secure connection of wires from 0.75 mm<sup>2</sup> to 2.5 mm<sup>2</sup>. Strong and robust mounting plate grid and high-quality self-retracting elements enable stable and secure installation in the box. Special springing elements facilitate

fitting the frame into the body.

Single flush-mounted French-type socket (2P+E) with two USB ports (1xUSB-A, 1xUSB-C; rated voltage: 5V, current: 2.8A). With the built-in USB charger, you can easily supply your phone or tablet. Intended for indoor use (IP20).

The product is available in three colours: white, black and anthracite. The dimensions measure: 81x81x11 mm.

## TECHNICAL DATA

### General information:

<b>Model:</b>	Ze stykiem ochronnym (bolec)
<b>Protective contact:</b>	Okrągły
<b>Number of units:</b>	1
<b>Number of modules (module system):</b>	1
<b>Number of phases:</b>	1
<b>Connection type:</b>	Zacisk śrubowy
<b>With enhanced contact protection:</b>	Nie
<b>Label space/information surface:</b>	Nie
<b>Colour:</b>	Antracyt
<b>Mounting method:</b>	Montaż podtynkowy
<b>Type of fastening:</b>	Montaż pazurkowy / -śrubowy
<b>Material:</b>	Tworzywo sztuczne
<b>Material quality:</b>	Tworzywo termoplastyczne
<b>Surface protection:</b>	Malowanie
<b>Surface finishing:</b>	Matowy
<b>Nominal current [A]:</b>	16
<b>Nominal voltage [V]:</b>	250
<b>Frequency [Hz]:</b>	50
<b>Suitable for degree of protection (IP):</b>	IP20
<b>Device width [mm]:</b>	81

Device height [mm]:	81
Device depth [mm]:	11
Min. depth of built-in installation box [mm]:	30