







# Flush-mounted double socket 2x2P Pearl, 16A, 250V, PT-5 P, white

Marka: Orno | Symbol: OR-OE-7706/2P/W | Ean: 5904988912407





#### PRODUCT DESCRIPTION

Modular series with a symmetrical frame plate system (for 1-, 2-, 3-, 4-, 5-modules) allowing the product to be mounted in both horizontal and vertical positions. The modern quick-connect mechanism (wires are connected by pushing them directly into the body) provides secure and safe wire installation and removal. The sockets are equipped with traditional screw connections. The internal design of the terminals guarantees secure connection of wires from 0.75 mm 1 to 2.5 mm 1. Strong and robust mounting plate grid and high-quality self-retracting elements enable stable and secure installation in the box. Special springing elements facilitate







fitting the frame into the body.

Double french-type socket, 2x2P. Designed for flush mounting. It should be used indoors (IP20).

The product is available in three colors: white, black and anthracite. Dimensions 81x102x36.5mm.

## **TECHNICAL DATA**

## General information:

| Model:                                  | CEE 7/1 bez uziemienia     |
|---|----------------------------|
| Protective contact:                     | Brak                       |
| Number of units:                        | 2                          |
| Number of phases:                       | 1                          |
| Connection type:                        | Zacisk śrubowy             |
| With enhanced contact protection:       | Nie                        |
| Label space/information surface:        | Nie                        |
| Colour:                                 | Biały                      |
| Mounting method:                        | Montaż podtynkowy          |
| Type of fastening:                      | Montaż pazurkowy /-śrubowy |
| Material:                               | Tworzywo sztuczne          |
| Material quality:                       | Tworzywo termoplastyczne   |
| Surface protection:                     | Malowanie                  |
| Surface finishing:                      | Błyszczący                 |
| Nominal current [A]:                    | 16                         |
| Nominal voltage [V]:                    | 250                        |
| Frequency [Hz]:                         | 50                         |
| Suitable for degree of protection (IP): | IP20                       |
| Device width [mm]:                      | 81                         |
| Device height [mm]:                     | 102                        |
| Device depth [mm]:                      | 17.5                       |











#### Min. depth of built-in installation box [mm]:

19













