

## LED rotary dimmer Pearl, 230V, 50Hz, Pmin:3W, Pmax:35W, SO-1P/LED, anthracite

Marka: Orno | Symbol: OR-OE-7716/LED/A | Ean: 5904988911189

**ORNO**


### PRODUCT DESCRIPTION

Modular series with a symmetrical frame plate system (for 1-, 2-, 3-, 4-, 5-modules) allowing the product to be mounted in both horizontal and vertical positions. The modern quick-connect mechanism (wires are connected by pushing them directly into the body) provides secure and safe wire installation and removal. The sockets are equipped with traditional screw connections. The internal design of the terminals guarantees secure connection of wires from 0.75 mm<sup>2</sup> to 2.5 mm<sup>2</sup>. Strong and robust mounting plate grid and high-quality self-retracting elements enable stable and secure installation in the box. Special springing elements facilitate

fitting the frame into the body.

The rotary dimmer is used to turn on and off and adjust the intensity of light in rooms. Switching on and off is done by pressing the knob while adjusting the intensity is done by turning the knob. The device can also be used in three-way switch or four-way switch installation. It should be used indoors (IP20).

The product is available in three colors: white, black and anthracite.

## TECHNICAL DATA

### General information:

<b>Assembly arrangement:</b>	Element systemu modułowego do osprzętu elektroinstalacyjnego
<b>Method of operation:</b>	Pokrętło
<b>Type of load:</b>	Uniwersalne i LED
<b>Mounting method:</b>	Montaż podtynkowy
<b>Type of fastening:</b>	Montaż pazurkowy / -śrubowy
<b>Material:</b>	Tworzywo sztuczne
<b>Material quality:</b>	Tworzywo termoplastyczne
<b>Colour:</b>	Antracyt
<b>Suitable for degree of protection (IP):</b>	IP20
<b>Nominal voltage [V]:</b>	250
<b>Rated current [A]:</b>	16
<b>Max. switching power LED [W]:</b>	7-110
<b>Power consumption [W]:</b>	3-35
<b>Connection type:</b>	Zacisk śrubowy
<b>Device width [mm]:</b>	81
<b>Device height [mm]:</b>	81
<b>Device depth [mm]:</b>	7.6

