

LED rotary dimmer Pearl, 230V, 50Hz, Pmin:3W, Pmax:35W, SO-1P/LED, white

ORNO

Marka: Orno | Symbol: OR-OE-7716/LED/W | Ean: 5904988911172



PRODUCT DESCRIPTION

Modular series with a symmetrical frame plate system (for 1-, 2-, 3-, 4-, 5-modules) allowing the product to be mounted in both horizontal and vertical positions. The modern quick-connect mechanism (wires are connected by pushing them directly into the body) provides secure and safe wire installation and removal. The sockets are equipped with traditional screw connections. The internal design of the terminals guarantees secure connection of wires from 0.75 mm² to 2.5 mm². Strong and robust mounting plate grid and high-quality self-retracting elements enable stable and secure installation in the box. Special springing elements facilitate

fitting the frame into the body.

The rotary dimmer is used to turn on and off and adjust the intensity of light in rooms. Switching on and off is done by pressing the knob while adjusting the intensity is done by turning the knob. The device can also be used in three-way switch or four-way switch installation. It should be used indoors (IP20).

The product is available in three colors: white, black and anthracite.

TECHNICAL DATA

General information:

Assembly arrangement:	Element systemu modułowego do osprzętu elektroinstalacyjnego
Method of operation:	Pokrętło
Type of load:	Uniwersalne i LED
Mounting method:	Montaż podtynkowy
Type of fastening:	Montaż pazurkowy / -śrubowy
Material:	Tworzywo sztuczne
Material quality:	Tworzywo termoplastyczne
Colour:	Biały
Suitable for degree of protection (IP):	IP20
Nominal voltage [V]:	250
Rated current [A]:	16
Max. switching power LED [W]:	7-110
Power consumption [W]:	3-35
Connection type:	Zacisk śrubowy
Device width [mm]:	81
Device height [mm]:	81
Device depth [mm]:	7.6