







## Surface-mounted double socket 2x2P+E, splash-proof with cover B2, IP54, NT-6B2, gray

Marka: Orno | Symbol: OR-OE-7806/G | Ean: 5904988911813

ORNO



## PRODUCT DESCRIPTION

The B2 series of sockets and switches, IP54 rated, dust and moisture resistant. The series features a timeless shape and robust housing. Perfect for installation in industrial facilities and households. The switches are equipped with quick connectors, while the sockets are equipped with traditional screw connections.

Double french-type socket 2x2P+E, splash-proof with cover. Designed for surface mounting. It will be suitable wherever protection against dust and water splashes is required (IP54).







The product is available in three colors: white, gray and gray-black. Dimensions 77x133x50mm.

## TECHNICAL DATA

## General information:

| Model:                                  | Ze stykiem ochronnym (bolec) |
|---|------------------------------|
| Protective contact:                     | Okrągły                      |
| Number of units:                        | 2                            |
| Number of phases:                       | 1                            |
| Connection type:                        | Zacisk śrubowy               |
| With hinged lid:                        | Tak                          |
| With enhanced contact protection:       | Nie                          |
| Label space/information surface:        | Nie                          |
| Colour:                                 | Szary                        |
| Mounting method:                        | Montaż natynkowy             |
| Type of fastening:                      | Montaż śrubowy               |
| Material:                               | Tworzywo sztuczne            |
| Material quality:                       | Tworzywo termoplastyczne     |
| Surface protection:                     | Malowanie                    |
| Surface finishing:                      | Błyszczący/Matowy            |
| Nominal current [A]:                    | 16                           |
| Nominal voltage [V]:                    | 250                          |
| Frequency [Hz]:                         | 50                           |
| Suitable for degree of protection (IP): | IP54                         |
| Device width [mm]:                      | 133                          |
| Device height [mm]:                     | 77                           |
| Device depth [mm]:                      | 50                           |















