

## DRACO LED NEW 1.5W, flush-mounted staircase luminaire, 12VDC, 30lm, 6000K, white, twilight and motion sensor

**ORNO**

Marka: Orno | Symbol: OR-OS-6164LR6/W | Ean: 5908254814303



### PRODUCT DESCRIPTION

LED staircase luminaire designed to provide decorative lighting to stairways, halls, walls, facades and other indoor traffic areas. The unique design of the luminaire, its fixture made of stainless steel and the use of LED technology make the product suitable for both – classic and modern interiors. In addition, the luminaire has been equipped with a motion sensor and a twilight sensor, thanks to which (depending on the settings) the

staircase lighting will only turn on when it detects movement or when light intensity is sufficiently low.

## TECHNICAL DATA

### General information:

|                                                                |                                                                       |
|----------------------------------------------------------------|-----------------------------------------------------------------------|
| Place of application:                                          | Inside                                                                |
| Possibility of cooperation with a dimmer:                      | No                                                                    |
| Durability L70/B50:                                            | 20000 h                                                               |
| Connection type:                                               | Free cable ends                                                       |
| The minimum distance from the illuminated object:              | 0,5 m                                                                 |
| Luminous flux:                                                 | 30 lm                                                                 |
| Rated power:                                                   | 1,5 W                                                                 |
| Light source:                                                  | LED SMD                                                               |
| Degree of protection (IP):                                     | 20                                                                    |
| Colour temperature:                                            | 3000                                                                  |
| Nominal voltage:                                               | 12V DC                                                                |
| Ambient temperature range to which the product may be exposed: | - 30 ~ 45 °C                                                          |
| Colour:                                                        | white                                                                 |
| Installation:                                                  | dopuszkowy - brak tłumaczenia                                         |
| Dimensions - depth:                                            | 45 mm                                                                 |
| Dimensions - width:                                            | 75 mm                                                                 |
| Dimensions - height:                                           | 75 mm                                                                 |
| Other features:                                                | PIR version - can manage max. 8 staircase luminaire in basic version. |
| Colour rendering index CRI:                                    | >80                                                                   |
| Weight:                                                        | 43 g                                                                  |
| Material housing:                                              | Steel plate                                                           |
| Detection angle:                                               | 120°                                                                  |
| Material of the lampshade:                                     | Acrylic glass                                                         |

|                                          |          |
|------------------------------------------|----------|
| Control of the motion sensor:            | Yes      |
| Number of on / off cycles:               | 10000    |
| Protection class against electric shock: | III      |
| Dimensions of the mounting hole:         | 60 mm    |
| Type of sensor:                          | PIR      |
| Detection range:                         | 2-3 m    |
| Daylight sensor adjustment range (LUX):  | <0-25lux |
| Lighting time adjustment range (TIME):   | 3-45s    |



