

Industrial power supply for a DIN rail, 12VDC, 10A, 120W, metal housing

Marka: **Orno** | Symbol: **OR-PSU-1673** | Ean: **5908254848322**

ORNO


PRODUCT DESCRIPTION

The industrial power supply for a DIN rail is a modern and versatile device for increasing the efficiency and safety of industrial installations in switchboards, switchgears or machines used in automation.

The unit provides a stable 12V DC output voltage with a maximum output current of 10A with up to 16A load capability. The 12-48V AC output voltage range allows to adjust its operation to different system requirements. An output power of 120W and a precise voltage stabilization guarantee efficient and reliable

power supply to the connected devices.

The unit is equipped with an advanced short-circuit, surge and current protection, increasing operational safety and securing both the power supply and the connected devices. It is Class II rated, therefore it meets the high safety standards required in industry.

It is intended for heavy-duty use. Its design facilitates air to flow freely, preventing overheating and supporting long-term, stable operation. Resistance to low and high temperatures further enhances the device's reliability in a variety of environments.

Activation of the power supply is indicated by a LED diode. In addition, it is equipped with a potential-free output, which allows more advanced control over the unit. Screws ensure permanent and secure wire connection. DIN rail mounting. Suitable for indoor use (IP20).

The power supply has compact dimensions (63x125x114 mm) to save space in switchboards and switchgears. The plastic housing and high-quality components ensure a long service life.

The device complies with standards: EN 55032 (CISPR32), EN 61204-3, EN 61000-3-2-3, EAC TP TC 020, CNS1348, UL508, EN 62368-1, EAC TP TC 004, CNS14336-1 AS/NZS 62368.1.

TECHNICAL DATA

General information:

Voltage type of supply voltage:	AC
1st secondary output voltage at DC [V]:	12
Max. output current 1 [A]:	10
Max. output current 2 [A]:	16
Max. Overload [%]:	160
Max. Overcurrent [V]:	240
Secondary voltage adjustable [V]:	12-48
Short-circuit-proof:	Tak
Rated supply voltage at AC 50 Hz [V]:	85-264
Rated supply voltage at AC 60 Hz [V]:	85-264
Output voltage stabilized:	Tak
Line Regulation:	±0,5%

Power output [W]:	120
Efficiency:	0.855
Stabilized:	Tak
Type of electric connection:	Połączenie Śrubowe
Rail mounting possible:	Tak
Wall mounting possible:	Nie
Direct mounting possible:	Nie
Width [mm]:	63
Height [mm]:	125
Depth [mm]:	114
Degree of protection (IP):	IP20
Operating Temperature:	-20 - +70
Storage Temp:	-40 - +85
Storage Humidity(RH)::	10 - 95%
Working Humidity(RH): / wilgotność podczas pracy (bez kondensacji):	20 - 90%
Compliance with standards:	EN 55032 (CISPR32), EN 61204-3, EN 61000-3-2-3, EAC TP TC 020, CNS1348, UL508, EN 62368-1, EAC TP TC 004, CNS14336-1 AS/NZS 62368.1