

## Smoke detector, 1x9V DC

Marka: **Virone** | Symbol: **SD-3** | Ean: **5908254850424**

**ViRONE**



### PRODUCT DESCRIPTION

A battery-operated smoke detector is a device that identifies smoke particles in a closed room and alerts of the danger at an early stage of a possible fire. The photoelectric smoke detector works well as an additional means of monitoring the hazard and thus protecting wherever there is a risk of fire ignition.

The small and lightweight autonomous smoke detector is designed for self-assembly and operation. Powered by included 6LR61 or 6F22 batteries. The device alarms of danger (the alarm volume is 85dB) and also

indicates when to replace a depleting battery. In addition, it is equipped with LED for visual indication.

The lifetime of the sensor is 10 years and the whole device is compliant with standards: EN 14604:2006+AC:2009, EN 14604:2005/AC1:2008 as certified by ANPI. The battery-operated smoke detector also has a TEST button to check that the device is functioning correctly.

## TECHNICAL DATA

### General information:

Operating principle:	Optyczny
Optical notification:	Tak
Acoustic notification:	Tak
Loudness [dB(A)]:	≥85db/3m
Response temperature [°C]:	-10°C ~ +40°C
Smoke switcher:	Tak
Type of test- /pause button:	Kombinowany
Mounting method:	Montaż powierzchniowy
Self-adhesive:	Nie
Standalone:	Tak
Current supply primary:	Bateria/akumulator
Voltage type (supply voltage):	DC
Supply voltage DC [V]:	9
With backup battery:	Tak
Battery included:	Tak
Voltage type (operating voltage):	DC
Operating voltage DC [V]:	9
Colour:	Biały
Degree of protection (IP):	IP20
Height/depth [mm]:	36
Diameter [mm]:	102

Type of sensor:	fotoelektryczny
Sensor lifetime:	10 lat
Compliant standards:	EN 14604:2005+AC:2008; PN-EN 14604:2006+AC:2009
Certification authority:	ANPI
Manufacturer name:	NINGBO KINGDUN ELECTRONIC INDUSTRY CO.,LTD. NO.8 FENGYUAN ROAD,SOUTH OF ECONOMIC DEVELOPMENT AREA,YUYAO CITY, ZHEJIANG PROVINCE CHINA