

## WALLIE LED Solar lamp 2-in-1 ,2 W, 150 lm, IP54, 3000/6500 K, 1200 mAh

**ViRONE**Marka: **Virone** | Symbol: **SL-1** | Ean: **5908254852435**

### PRODUCT DESCRIPTION

You can use the WALLIE solar lamp to illuminate your garden, facade, paths, driveway or entrance. It is powered by a battery charged during the day by a built-in solar panel. When weather conditions do not allow for effective charging, you can use a charger and USB-C cable (cable included).

Two mounting methods are available. You can mount the lamp on the wall or stick it directly into the ground, depending on the place you want to illuminate. The 360° adjustable head allow you to position the solar

panel and light source in the desired direction.

You can choose the colour temperature of the light – warm 3000 K or cold 6500 K. You have four lighting modes at your disposal: a weaker or stronger beam of light in a warm colour and a weaker or stronger beam in a cold colour. The built-in twilight sensor causes the floodlight to turn on automatically at dusk and off at dawn.

The built-in 1200 mAh battery can be charged using a solar panel (approx. 6–8 hours) or via USB-C (2–3 hours). When fully charged, the lamp lights for 6–8 hours, depending on the selected operating mode.

The IP54 rated housing protects the device against dust and water splashes, so you can use it outdoors. The lamp is suitable for everyday use around the house, without the need for running cables or connecting to the mains.

## TECHNICAL DATA

### General information:

Nominal voltage [V]:	3.7
Lamp type:	LED, niewymienne
Suitable for lamp power [W]:	2
Rated luminous flux according to IEC 62722-2-1 [lm]:	150
With light source:	tak
Colour temperature [K]:	3000/6500
Rated life time L70/B50 at 25 °C [h]:	10000
Colour rendering index CRI:	70–79
Colour of light:	Wielobarwny
Degree of protection (IP):	IP54
Type of luminaire:	Reflektory ogrodowe
Material housing:	Tworzywo sztuczne
Colour housing:	Czarny
Material cover:	Tworzywo sztuczne przezroczyste
With solar panel:	tak
Type of solar panel:	Panel polikrystaliczny 5V 1,5W

<b>Width [mm]:</b>	95
<b>Height/depth [mm]:</b>	270
<b>Length [mm]:</b>	158
<b>Voltage type:</b>	DC
<b>Colour temperature adjustable:</b>	Krokowo
<b>Luminous flux adjustable:</b>	Krokowo
<b>Other features:</b>	Akumulator 1200 mAh, ładowany przez panel solarny (6-8h) lub przez kabel USB-C (2-3h); czas pracy 6-8h





