

Rechargeable LED work light, 5+3W, 300lm+70lm, 600mAh, magnet, clip

Marka: **Virone** | Symbol: **WL-16** | Ean: **5908254851278**



PRODUCT DESCRIPTION

The LED work light is a functional lighting device intended for use in garages, workshops, construction sites or at home. It combines handiness, mobility and efficiency of use, providing irreplaceable support for all types of technical and service work.

The built-in 600mAh Li-ion battery ensures continuous operation without the need to purchase and replace additional batteries. The device is charged via the popular USB-C port (cable not included). A 3-stage

battery charge indicator helps to monitor energy levels to avoid draining the device.

The product is equipped with two light sources: a 5W main LED COB panel with 300lm luminous flux and a 3W top LED spotlight with 70lm luminous flux. 4 modes of operation are available: COB in 100% and 50% mode and top LED light in 100% and 50% mode. The LED COB technology ensures energy efficiency, as well as an even dispersion of light with a cold colour of 7500K.

Two built-in magnets - one in the base and the other on the clip - enable the work light to be securely attached to metal surfaces. The practical clip allows it to be attached to work trousers, a pocket or a bag. Each of these is extremely useful when the user needs free hands and to illuminate a specific space.

The handy and lightweight design makes the product easy to carry and convenient for everyday use. The work light is made of durable plastic in black-grey. Dimensions: 168x20x23 mm.

The product is sold as a display of 12 pieces.

TECHNICAL DATA

General information:

Lamp type:	LED, niewymienne
Power [W]:	5+3
Luminous flux [lm]:	300+70
Power type:	Akumulator Li-ion
Battery capacity [mAh]:	600
Battery type:	Akumulator zainstalowany na stałe
Number of batteries:	1
With batteries:	tak
Number of light modes:	4
Modes of operation:	LED COB 100%, LED COB 50%, górna dioda LED 100%, górna dioda LED 50%
Rechargeable:	tak
Battery charge indicator:	tak
Light range [m]:	45
Color temperature [K]:	7500

Color rendering index Ra/CRI:	70
Lifespan L70/B50 [h]:	20000
Number of switching cycles:	10000
Impact protection IK (shock resistance):	IK03
Model:	Robocze-warsztatowe
Material:	Tworzywo sztuczne
Colour housing:	Czarny/Szary
Length/height [mm]:	168
Width [mm]:	20
Depth [mm]:	23
Weight total [g]:	55
The ports:	USB-C
Additional information:	Klips, dwa magnesy
Rechargeable:	tak
With light source:	tak